


## Adapters

### MMS Male female thread tee

Male NPTF\* thread (SAE J476) / Female NPTF\* thread (SAE J476)

SAE 140425

\*Stainless Steel = NPT to prevent galling



Thread NPT/NPTF PTM	Thread NPT/NPTF PTF	D mm	D1 mm	N mm	N1 mm	Y mm	Weight (steel) g/1 piece	Adapter Steel	Adapter Stainless Steel	PN (bar)	
										S	SS
1/8-27	1/8-27	4.8	8.3	20	17	14.0	45	<b>1/8 MMS-S</b>	<b>1/8 MMS-SS</b>	350	350
1/4-18	1/4-18	7.1	10.7	28	22	19.0	118	<b>1/4 MMS-S</b>	<b>1/4 MMS-SS</b>	350	350
3/8-18	3/8-18	10.3	14.2	31	26	22.0	126	<b>3/8 MMS-S</b>	<b>3/8 MMS-SS</b>	310	310
1/2-14	1/2-14	13.5	17.5	37	31	27.0	272	<b>1/2 MMS-S</b>	<b>1/2 MMS-SS</b>	210	210
3/4-14	3/4-14	18.3	22.8	40	35	33.3	408	<b>3/4 MMS-S</b>	<b>3/4 MMS-SS</b>	210	210
1-11.5	1-11.5	23.8	28.6	50	41	41.0	606	<b>1 MMS-S</b>	<b>1 MMS-SS</b>	125	120

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.