

**Other designs in series 26**

The following other designs can be found from page:

► Brass / Steel

P. 58

Safety coupling with a self-venting system. Self-venting takes place during disconnection – no risk of pressurised hoses being tossed around. When the sleeve is pulled back, the plug is released yet remains locked in. The coupling valve closes and the air is vented from the air line at the same time. Only then, by operating the sleeve again, can uncoupling take place safely. The system fulfils the requirements of ISO 4414 – increased safety standards in the work place. The plastic sleeve does not scratch working surfaces.

Series 26 with additional end connections available on request.

**Working Pressure****

12 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass nickel plated

Plug: Steel zinc plated

Seals: NBR

Technical Description

Connecting Force 0 bar: 40 N

Connecting Force 6 bar: 100 N

Safety Note

Reliable functioning can only be guaranteed in conjunction with original Parker Rectus plugs made of steel.


Working Temperature*

-20°C up to +60°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +60°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

Flow diagrams




Air





Couplings – with valve




Series 26KE

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	G 1/4	22	55	9	31	26KEAW13MPN
	G 3/8	22	55	9	31	26KEAW17MPN
	G 1/2	24	58	12	31	26KEAW21MPN
 Female Thread	G 1/4	22	57	9	31	26KEIW13MPN
	G 3/8	22	57	9	31	26KEIW17MPN
	G 1/2	24	60	12	31	26KEIW21MPN
 Hose Barb	6 mm	22	71	25	31	26KETF06MPN
	8 mm	22	71	25	31	26KETF08MPN
	9 mm	22	71	25	31	26KETF09MPN
	10 mm	22	71	25	31	26KETF10MPN
	13 mm	22	71	25	31	26KETF13MPN



Plugs – without valve

Series 25SF

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 Male Thread	R 1/8	13	33	9		25SFAK10SXZ
	R 1/4	14	37	12		25SFAK13SXZ
	R 3/8	17	37	12		25SFAK17SXZ
	R 1/2	22	43	17		25SFAK21SXZ
 Female Thread	G 1/8	14	30	7		25SFIW10SXZ
	G 1/4	17	33	9		25SFIW13SXZ
	G 3/8	19	33	9		25SFIW17SXZ
	G 1/2	24	36	12		25SFIW21SXZ
 Hose Barb	6 mm		48	25	12	25SFTF06SXZ
	8 mm		48	25	12	25SFTF08SXZ
	9 mm		48	25	12	25SFTF09SXZ
	10 mm		48	25	12	25SFTF10SXZ
	13 mm		48	25	12	25SFTF13SXZ