

Specifications:

| Model Number | Port Size | Max. Pressure | Max. Temp. | Materials of Construction | | | Seals | Sump Capacity | Weight | Dimensions | |
|--------------|-----------|------------------------|------------------|---------------------------|-----------------|----------|---------------|--------------------|---------------------|-------------------|---------------------|
| | | | | Head | Internals | Bowl | | | | Length | Width |
| FFC-213 | 1/2" NPT | 3600 PSIG (248 bar) | 221°F (105°C) | Aluminum | Stainless Steel | Aluminum | Fluoro-carbon | 5.0 oz (148 ml) | 3.5 lbs (1.6 kg) | 8.43" (214 mm) | 3.25" (82.55 mm) |
| FFC-213-SAE | SAE-8 | | | | | | | | | | |

Flow Rates in Natural Gas (SCFM):

| Filter Housing Model | Media Grade | Coalescing Efficiency | 100 PSIG | 250 PSIG | 500 PSIG | 750 PSIG | 1000 PSIG | 1500 PSIG | 2000 PSIG | 2500 PSIG | 3000 PSIG | 3600 PSIG |
|----------------------|-------------|-----------------------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|
| All FFC-213 Models | 6 | 99.97% | 37 | 84 | 164 | 244 | 324 | 483 | 643 | 802 | 962 | 1153 |
| | 10 | 95% | 51 | 141 | 274 | 407 | 539 | 805 | 1071 | 1337 | 1603 | 1922 |

How to Order:

| | | | | |
|----------------|---|---|---|-----------------------|
| FFC-213 | — | SAE | — | 10 |
| Series Name | | Port | | Media Grade |
| FFC-213 | | Omit for 1/2" NPT SAE = SAE-8 | | 6 10 |

Examples: FFC-213-6, FFC-213-SAE-10

Replacement Element Kits:

| Filter Housing Model | Media Grade 6 | Media Grade 10 |
|----------------------|---------------|----------------|
| All FFC-213 Models | DLS113-6K | DLS113-10K |

Replacement Element kits include element, head-to-bowl o-ring, and lubricant.

Mounting Bracket Kit: 2222FFC

Kit includes bracket and 2 cap screws.

