

ISO B



Technical Data

max. Working Pressure 12 bar

Temperature Range -20°C up to +100°C (NBR)

Flow rate 675 l/min.
At input pressure 6 bar, pressure drop 0.6 bar

Material

Coupling: Anodised Aluminium, Nickel plated brass
 Plug: Nickel plated steel
 Seal: NBR

Coupler - Male Thread



C	Part Number
G 1/4	24KPAW13APX
G 3/8	24KPAW17APX
G 1/2	24KPAW21APX

Plug - Male Thread



C	Part Number
R 1/4	23SFAK13SXN
R 3/8	23SFAK17SXN
R 1/2	23SFAK21SXN

Coupler - Female Thread



C	Part Number
G 1/4	24KPIW13APX
G 3/8	24KPIW17APX
G 1/2	24KPIW21APX

Plug - Female Thread



C	Part Number
G 1/4	23SFIW13SXN
G 3/8	23SFIW17SXN
G 1/2	23SFIW21SXN

Coupler - Hose Barb



I.D. Hose	Part Number
6 mm	24KPTF06APX
8 mm	24KPTF08APX
10 mm	24KPTF10APX

Plug - Hose Barb



I.D. Hose	Part Number
6 mm	23SFTF06SXN
8 mm	23SFTF08SXN
10 mm	23SFTF10SXN