

Push-Button-Technology

Series 30KP

Nominal Diameter
8,0

Technical Data

max. Working Pressure	12 bar
Temperature Range	-20°C up to +100°C (NBR)
Flow rate <small>At input pressure 6 bar, pressure drop 0,6 bar</small>	1.470 l/min.
Material	Coupling: Anodised Aluminium, Nickel plated brass Plug: Nickel plated steel Seal: NBR



ISO B

Coupler - Male Thread

	C	Part Number
	G 1/4	30KPAW13APX
	G 3/8	30KPAW17APX
	G 1/2	30KPAW21APX

Plug - Male Thread

	C	Part Number
	G 1/4	30SFAW13SXN
	G 3/8	30SFAW17SXN
	G 1/2	30SFAW21SXN

Coupler - Female Thread

	C	Part Number
	G 1/4	30KPIW13APX
	G 3/8	30KPIW17APX
	G 1/2	30KPIW21APX

Plug - Female Thread

	C	Part Number
	G 1/4	30SFIW13SXN
	G 3/8	30SFIW17SXN
	G 1/2	30SFIW21SXN

Coupler - Hose Barb

	I.D. Hose	Part Number
	8 mm	30KPTF08APX
	10 mm	30KPTF10APX

Plug - Hose Barb

	I.D. Hose	Part Number
	8 mm	30SFTF08SXN
	10 mm	30SFTF10SXN