


Klemmring
Bague de serrage
Compression ferrule

SO 50001

Type -d	Mat.-Nr.	bar	L	D	z	e	kg/100
Für metrische Rohre	Pour tubes métriques		For metric tubes				
SO 50001-2	056.0010.020	250	3.5	5.0	0.7	1.5	0.020
SO 50001-3	056.0010.030	250	4.5	5.0	0.9	2.5	0.030
SO 50001-4	056.0010.040	250	5.0	6.0	1.0	3.5	0.050
SO 50001-5	056.0010.050	250	5.5	6.8	1.1	4.0	0.050
SO 50001-6	056.0010.060	200	6.5	8.5	1.2	4.5	0.120
SO 50001-8	056.0010.080	200	7.0	10.5	1.2	6.5	0.170
SO 50001-10	056.0010.100	160	7.8	12.7	1.2	8.5	0.260
SO 50001-12	056.0010.120	160	8.8	14.7	1.2	10.0	0.330
SO 50001-15	056.0010.150	100	10.0	18.0	1.4	13.0	0.510
SO 50001-18	056.0010.180	100	12.0	22.0	1.4	16.0	1.030
SO 50001-22	056.0010.220	64	13.5	26.0	1.4	20.0	1.260
SO 50001-28	056.0010.280	40	15.4	32.5	2.0	24.0	2.440

Für Zollrohre	Pour tubes pouces		For inch tubes				
SO 50001-3,2	056.0010.032	250	4.5	5.0	0.9	2.5	0.030
SO 50001-6,35	056.0010.063	200	6.5	8.5	1.2	4.5	0.110
SO 50001-7,94	056.0010.079	200	7.0	10.5	1.2	6.5	0.180
SO 50001-9,52	056.0010.095	160	7.8	12.7	1.2	8.0	0.300
SO 50001-12,7	056.0010.127	160	10.5	18.0	1.5	11.0	0.740

Umrechnung für "d" bei Zollrohren:

3,2 = 1/8
 6,35 = 1/4
 7,94 = 5/16
 9,52 = 3/8
 12,7 = 1/2

Conversion de "d" pour tubes en pouces:

3,2 = 1/8
 6,35 = 1/4
 7,94 = 5/16
 9,52 = 3/8
 12,7 = 1/2

Conversion for "d" for inch tubes:

3,2 = 1/8
 6,35 = 1/4
 7,94 = 5/16
 9,52 = 3/8
 12,7 = 1/2