

528N – Electrically non-conductive hose

Performance exceeds SAE 100 R8 /

ISO 3949 Type R8 / DIN EN 855 Type R8



- MAIN FEATURES

 - Electrically non-conductive
 - Very small hose outer diameters
 - Excellent abrasion resistance
 - Small bend radii
 - Low weight
 - Excellent chemical resistance due to polyamide core tube
- APPLICATIONS

High pressure service for general industrial and mobile hydraulic applications, where a non-conductive hose is required.

- CONSTRUCTION

Core tube

: Polyamide

Pressure reinforcement

: One braided layer of high tensile aramide fibre

Cover

: Polyurethane, not pinpricked

Colour

: orange

TEMPERATURE RANGE

-40°C up to +100°C for petroleum or synthetic hydraulic fluids.

Visit the webpage

Part No. #	DN	size	mm	inch	mm	Max. working pressure MPa / psi		Min. burst pressure MPa / psi		Min. bend radius mm	Weight kg/m	Fittings
528N-3	5	-03	4.8	3/16	10.6	34.5	5,000	138.0	20,000	38	0.07	56
528N-4	6	-04	6.3	1/4	12.7	34.5	5,000	138.0	20,000	51	0.10	56
528N-5	8	-05	7.9	5/16	14.5	31.0	4,500	124.0	18,000	64	0.12	56
528N-6	10	-06	9.5	3/8	16.1	27.5	4,000	110.0	16,000	64	0.13	56
528N-8	12	-08	12.7	1/2	20.4	24.0	3,500	96.0	14,000	102	0.20	56

- NOTES

 - Electrically non-conductive acc. to SAE J517 (less than 50 µA leakage under 250,000 Volts per meter).
 - Not recommended for forklift boom applications.