

DRINCONN ULTRAFOOD SPL









[EN] Mandrel built food hose suitable for suction and delivery of olive oil and fatty foodstuffs (milk etc...)



[EN] **TUBE:** White NBR rubber, resistant to vegetable oils and animal fats.

REINFORCEMENT: high tensile textile plies and galvanized steel helix wire

COVER: blue, smooth rubber, vegetable fats resistant, abrasion, ozone and weather resistant. Fabric impression

							
mm	mm	bar	bar	bar	kg/mt	mm	mt
19	29	10	30	0,9	0,50	57	20/40/60
25	35	10	30	0,9	0,65	75	20/40/60
30	40	10	30	0,9	0,74	90	20/40/60
32	42	10	30	0,9	0,80	96	20/40/60
35	45	10	30	0,9	0,85	105	20/40/60
38	49	10	30	0,9	0,95	114	20/40/60
40	50	10	30	0,9	0,98	120	20/40/60
51	62	10	30	0,9	1,30	153	20/40/60
60	72	10	30	0,9	1,50	180	20/40/60
70	82	10	30	0,8	2,10	280	20/40/60
76	89	10	30	0,8	2,35	300	20/40/60
80	94	10	30	0,8	2,45	320	20/40/60
90	103	5	15	0,8	3,00	360	20/40/60
102	115	5	15	0,8	3,40	400	20/40/60
120	136	5	15	0,8	4,70	480	20/40/60
125	141	5	15	0,8	4,85	500	20/40/60

-20°C / +90°C steam
cleaning up to +130°C
for max 20 minutes
-4°F / +194°F

NORMS: F.D.A, 3° sanitary standards and with BfR recommendations XXI cat.2, REG CE 1935/04 and 2023/06 DM 21/03/73. Free from phthalates – BPA – Bisphenol A

MARKING: EUROCORD® ULTRAFOOD
MULTIPURPOSE S/D DM 21/03/73 – CE 1935 – FDA
– 3° - BfR – PHTALATES FREE