


Nickel-Plated Brass Adaptors

0191

Tailpiece Adaptor for Rubber Hose, Male BSPP Thread


Nickel-plated brass

ØD	ØD1	C		E	F	K	L	kg
4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
7	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
	9	G1/2	0191 07 21	11	27	7	29.5	0.065
10	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
	12.2	G1/2	0191 10 21	11	27	7	29.5	0.061
13	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
	15.2	G1/2	0191 13 21	11	27	7	29.5	0.058
16	18.5	G1/2	0191 16 21	11	27	7	36.5	0.067

0931

Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

Nickel-plated brass


ØD	ØD1	C		E	F	K	L	kg
6	7	G1/8	0931 06 10	6	12	4	20	0.009
	7	G1/4	0931 06 13	8	14	5	20	0.013
	8	G1/8	0931 07 10	6	12	4	20	0.009
7	8	G1/4	0931 07 13	8	14	5	20	0.013
	8	G3/8	0931 07 17	9	19	5	20	0.022
	9	G1/8	0931 08 10	6	12	4	20	0.009
8	9	G1/4	0931 08 13	8	14	5	20	0.014
	9	G3/8	0931 08 17	9	19	5	20	0.022
	12	G1/4	0931 10 13	8	14	5	20	0.016
10	12	G3/8	0931 10 17	9	19	5	20	0.024
	12	G1/2	0931 10 21	10	22	6	22	0.031
	17	G3/8	0931 15 17	9	19	6	24	0.030
15	17	G1/2	0931 15 21	10	22	6	24	0.037
	18	G1/2	0931 18 21	10	22	6	24	0.039

0934

Hose Barb Adaptor, Male BSPT Thread

New

Nickel-plated brass

	ØD	C		F	L	L1	kg
6	R1/8		0934 06 10	12	31.5	19	0.009
	R1/4		0934 06 13	14	35	19	0.014
7	R1/8		0934 07 10	12	31.5	19	0.009
	R1/4		0934 07 13	14	35	19	0.014
8	R1/8		0934 08 10	12	31.5	19	0.010
	R1/4		0934 08 13	14	35	19	0.015
	R1/8		0934 09 10	12	31.5	19	0.012
9	R1/4		0934 09 13	14	35	19	0.015
	R3/8		0934 09 17	17	35.5	19	0.021
	R1/2		0934 09 21	22	38.5	19	0.032
10	R1/8		0934 10 10	12	32.5	20	0.010
	R1/4		0934 10 13	14	36	20	0.015
	R3/8		0934 10 17	17	36.5	20	0.022
	R1/2		0934 10 21	22	39.5	20	0.033
12	R1/4		0934 12 13	14	36	20	0.019
	R3/8		0934 12 17	17	36.5	20	0.021
	R1/2		0934 12 21	22	39.5	20	0.033
14	R3/8		0934 14 17	17	38.5	22	0.023
	R1/2		0934 14 21	22	41.5	22	0.036
16	R3/8		0934 16 17	17	38.5	22	0.026
	R1/2		0934 16 21	22	41.5	22	0.038
	R3/4		0934 16 27	27	45	22	0.062
17	R3/8		0934 17 17	18	40.5	24	0.030
	R1/2		0934 17 21	22	43.5	24	0.043
18	R3/8		0934 18 17	19	40.5	24	0.031
	R1/2		0934 18 21	22	43.5	24	0.043
	R3/4		0934 18 27	27	47	24	0.062
20	R3/8		0934 20 17	22	41	24	0.038
	R1/2		0934 20 21	22	43.5	24	0.046