


## 13B8X – BSP Male - 60° Cone




### 8X Series

Part No. #	DN size mm inch				Connection Type Thread Size	A mm	B mm	J mm
13B8X-4-025	4	-025	4.0	5/32	G 1/4	57	30	17
13B8X-4-04	6	-04	6.4	1/4	G 1/4	64	32	17
13B8X-6-04	6	-04	6.4	1/4	G 3/8	67	35	19
13B8X-6-05	8	-05	7.9	5/16	G 3/8	69	30	22
13B8X-6-06	10	-06	9.5	3/8	G 3/8	70	30	22
13B8X-8-06	10	-06	9.5	3/8	G 1/2	75	35	22
13B8X-8-08	12	-08	12.7	1/2	G 1/2	79	36	24

**Material:** Steel, surface protection according to DIN 50 961 Fe/Zn, special materials available upon request

## 1018X – NPTF Male - 60° Cone



### 8X Series

Part No. #	DN size mm inch				Connection Type		A mm	B mm	H mm
					Thread Size	Tube OD 			
1018X-2-025	4	-025	4.0	5/32	1/8 - 27NPTF	2	51	24	8
1018X-4-025	4	-025	4.0	5/32	1/4 - 18NPTF	4	59	32	13
1018X-4-04	6	-04	6.4	1/4	1/4 - 18NPTF	4	65	33	14
1018X-6-04	6	-04	6.4	1/4	3/8 - 18NPTF	6	67	35	19
1018X-6-05	8	-05	7.9	5/16	3/8 - 18NPTF	6	70	30	19
1018X-6-06	10	-06	9.5	3/8	3/8 - 18NPTF	6	71	31	19
1018X-8-06	10	-06	9.5	3/8	1/2 - 14NPTF	8	76	36	22
1018X-8-08	12	-08	12.7	1/2	1/2 - 14NPTF	8	79	36	22

**Material:** Steel, surface protection according to DIN 50 961 Fe/Zn, special materials available upon request