







**CA – Female Metric 24° – Light Series with O-ring – Swivel – Straight**

ISO 12151-2-SWS-L – DKOL









 <b>Part Number</b> 	 <b>Hose I.D.</b>				 <b>Thread metric</b>	<b>Tube O.D.</b> mm	<b>A</b> mm	<b>B</b> mm	 <b>W</b> mm
	DN	Inch	Size	mm					
1CA48-6-4C	6	1/4	-4	6,3	M12x1,5	6	46	22	14
1CA48-8-4C	6	1/4	-4	6,3	M14x1,5	8	46	22	17
1CA48-10-5C	8	5/16	-5	7,9	M16x1,5	10	46	22	19
1CA48-12-5C	8	5/16	-5	7,9	M18x1,5	12	46	23	22
1CA48-10-6C	10	3/8	-6	9,5	M16x1,5	10	46	23	19
1CA48-12-6C	10	3/8	-6	9,5	M18x1,5	12	46	23	22
1CA48-15-8C	12	1/2	-8	12,7	M22x1,5	15	50	26	27
1CA48-18-10C	16	5/8	-10	15,9	M26x1,5	18	51	26	32
1CA48-22-10C	16	5/8	-10	15,9	M30x2	22	55	30	36
1CA48-22-12C	20	3/4	-12	19,1	M30x2	22	56	30	36
1CA48-28-16C	25	1	-16	25,4	M36x2	28	63	33	41
1CA48-35-20C	32	1-1/4	-20	31,8	M45x2	35	82	35	50
1CA48-42-24C	40	1-1/2	-24	38,1	M52x2	42	77	39	60

Hose fittings are delivered with ozone-resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -30 °C up to +105 °C. Hose fittings with special O-rings (Viton or EPDM) available on request. For O-ring dimensions and part numbers see Catalogue C4400/UK.

**CF – Female Metric 24° – Light Series with O-ring – Swivel – 90° Elbow**

ISO 12151-2-SW – DKOL 90°



 <b>Part Number</b> 	 <b>Hose I.D.</b>				 <b>Thread metric</b>	<b>Tube O.D.</b> mm	<b>A</b> mm	<b>B</b> mm	<b>E</b> mm	 <b>W</b> mm
	DN	Inch	Size	mm						
1CF48-8-4C	6	1/4	-4	6,3	M14x1,5	8	51	28	29	17
1CF48-10-5C	8	5/16	-5	7,9	M16x1,5	10	61	37	29	19
1CF48-10-6C	10	3/8	-6	9,5	M16x1,5	10	60	37	37	19
1CF48-12-6C	10	3/8	-6	9,5	M18x1,5	12	58	35	36	22
1CF48-15-8C	12	1/2	-8	12,7	M22x1,5	15	61	37	43	27
1CF48-18-10C	16	5/8	-10	15,9	M26x1,5	18	66	41	45	32
1CF48-22-12C	20	3/4	-12	19,1	M30x2	22	80	54	55	36
1CF48-28-16C	25	1	-16	25,4	M36x2	28	100	70	71	41
1CF48-35-20C	32	1-1/4	-20	31,8	M45x2	35	130	83	79	50
1CF48-42-24C	40	1-1/2	-24	38,1	M52x2	42	138	101	101	60

Standard hose fittings are delivered with ozone-resistant Nitrile O-ring. For O-ring dimensions and part numbers see Catalogue C4400/UK.