








**1C – Female Metric 24° – Heavy Series with O-ring – Swivel – 90° Elbow**

ISO 12151-2-SWE-S – DKOS 90°










 Part Number  48	 Hose I.D.				 Thread metric	 Tube O.D. mm	A mm	B mm	E mm	 W mm
	DN	Inch	Size	mm						
11C48-8-4C	6	1/4	-4	6,3	M16x1,5	8	50	26	29	19
11C48-10-4C	6	1/4	-4	6,3	M18x1,5	10	50	26	29	22
11C48-12-5C	8	5/16	-5	7,9	M20x1,5	12	60	36	32	24
11C48-12-6C	10	3/8	-6	9,5	M20x1,5	12	58	35	37	24
11C48-14-6C	10	3/8	-6	9,5	M22x1,5	14	58	35	37	27
11C48-16-8C	12	1/2	-8	12,7	M24x1,5	16	61	37	45	30
11C48-20-10C	16	5/8	-10	15,9	M30x2	20	65	40	48	36
11C48-20-12C	20	3/4	-12	19,1	M30x2	20	80	54	58	36
11C48-25-12C	20	3/4	-12	19,1	M36x2	25	80	54	59	46
11C48-30-16C	25	1	-16	25,4	M42x2	30	105	75	75	50

Hose fittings are delivered with ozone-resistant Nitrile (NBR) O-ring as a standard version.  
Working temperature from -30 °C up to +105 °C. Hose fittings with special O-rings (Viton or EPDM) available on request. For O-ring dimensions and part numbers see Catalogue C4400/UK.

**D2 – Male Metric 24° – Heavy Series – Rigid – Straight**

ISO 12151-2-S-S – CES



 Part Number  48	 Hose I.D.				 Thread metric	 Tube O.D. mm	A mm	B mm	 H mm
	DN	Inch	Size	mm					
1D248-10-4C	6	1/4	-4	6,3	M18x1,5	10	50	26	19
1D248-12-5C	8	5/16	-5	7,9	M20x1,5	12	50	26	22
1D248-14-6C	10	3/8	-6	9,5	M22x1,5	14	51	28	22
1D248-16-8C	12	1/2	-8	12,7	M24x1,5	16	53	29	24
1D248-20-10C	16	5/8	-10	15,9	M30x2	20	58	32	30
1D248-25-12C	20	3/4	-12	19,1	M36x2	25	64	38	36
1D248-25-16C	25	1	-16	25,4	M36x2	25	69	39	36

Information about standard products or non-standard products can be found in the current price list.  
Dimensions shown may be changed at any time without prior notice.