

# Midi Series

Without Shut-Off



Single Shut-Off




**0172**

## Coupler, Female BSPP Thread



Nickel-plated brass, NBR



DN	C		E	F	G	L	kg
12	G3/8	<a href="#">0172 12 17</a>	16	27	29	56	0.155
	G1/2	<a href="#">0172 12 21</a>	16	27	29	56	0.142


Midi series: single shut-off = 2200 NI/min

**2272**

## Coupler, Straight-Through, Female BSPP Thread



Nickel-plated brass, NBR




DN	C		E	F	G	L	kg
12	G1/2	<a href="#">2272 12 21</a>	10	24	29	33	0.072
	G3/4	<a href="#">2272 12 27</a>	10	30	29	34.5	0.074
	G1	<a href="#">2272 12 34</a>	10	36	29	34.5	0.087

**2511**

## Coupler with Barb Connection for Hose



Nickel-plated brass, NBR



DN	ØD	ØD1		G	L	L1	kg
12	12	13.5	<a href="#">2511 12 12</a>	29	75	32	0.146
	15	16.5	<a href="#">2511 12 15</a>	29	75	32	0.147
	19	20.5	<a href="#">2511 12 19</a>	29	81	38	0.159


Midi series: single shut-off = 2200 NI/min

**2297**

## Coupler, Straight-Through, with Barb Connection for Hose



Nickel-plated brass, NBR




DN	ØD	ØD1		G	L	L1	kg
12	12	13.5	<a href="#">2297 12 12</a>	29	51	27	0.073
	15	16.5	<a href="#">2297 12 15</a>	29	51	27	0.076
	19	20.5	<a href="#">2297 12 19</a>	29	57	33	0.090

**2294**

## Probe, Straight-Through, Male BSPP Thread



Nickel-plated brass



DN	C		E	F	L	kg
12	G3/8	<a href="#">2294 12 17</a>	6	22	31.5	0.031
	G1/2	<a href="#">2294 12 21</a>	9.5	22	37	0.044
	G3/4	<a href="#">2294 12 27</a>	13.5	27	41	0.068
	G1	<a href="#">2294 12 34</a>	10.5	34	36	0.072

Probe without shut-off

# Midi Series





Without Shut-Off







Single Shut-Off







## 0196 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated brass			C			E	F	L	kg
12	G1/4	0196 12 13		12	17	16	0.027			
	G3/8	0196 12 17		12	21	15	0.034			
	G1/2	0196 12 21		14	26	17	0.050			
Probe without shut-off										





## 2296 Probe, Straight-Through, Female BSPP Thread

	Nickel-plated brass			C			E	G	L	kg
12				G1/2	2296 12 21		11	24	31.5	0.031
				G3/4	2296 12 27		11	30	38	0.058
				G1	2296 12 34		11	36	36.5	0.058
Probe without shut-off										

## 0195 Probe, Straight-Through, with Barb Connection for Flexible Tubing

	<p>Nickel-plated brass</p> 		<b>ØD</b>	<b>ØD1</b>		<b>F</b>	<b>L</b>	<b>kg</b>
		12	7	9	0195 07 00	17	29.5	0.026
			10	12.2	0195 10 00	17	29.5	0.028
			13	15.2	0195 13 00	17	29.5	0.030
			16	18.5	0195 16 00	21	36.5	0.048
Probe without shut-off								

## 2295 Probe, Straight-Through, with Barb Connection for Flexible Hose

			<b>ØD</b>	<b>ØD1</b>		<b>G</b>	<b>L</b>	<b>L1</b>	<b>kg</b>
		12	12	13.5	<a href="#">2295 12 12</a>	17	48	27	0.026
			15	16.5	<a href="#">2295 12 15</a>	18	48	27	0.034
			19	20.5	<a href="#">2295 12 19</a>	24	57	33	0.053
Probe without shut-off									

## 2293 Y Coupler, Straight-Through

	Nickel-plated brass, NBR		DN			G	H	kg
12					2293 12 00	29	27	0.139
Probe without shut-off Midi Series: straight-through = 2200 NI/min								

# Midi Series

Without Shut-Off



Single Shut-Off



## 2270 Coupler with Tap, Male BSPP Thread

	Nickel-plated brass, NBR			<b>C</b>		<b>F</b>	<b>G</b>	<b>H</b>	<b>M</b>	<b>kg</b>
						28	29	40.5	35	0.272
						Flow = 2200 NI/min				

## 2203 Plug

	Nickel-plated brass				<b>G</b>	<b>L</b>	<b>kg</b>
					20	34	0.042
					2203 12 00		

## 2292 Universal Coupler Adaptor

	Nickel-plated brass, NBR				<b>G</b>	<b>L</b>	<b>kg</b>
					29	40.5	0.083
					2292 12 00		

Without shut-off  
This adaptor provides interchangeability with numerous components (especially watering accessories).

## 2398 Universal Probe Adaptor

	Nickel-plated brass, NBR				<b>G</b>	<b>L</b>	<b>L1</b>	<b>L2</b>	<b>kg</b>
					20	43	19	18.5	0.035
					2398 12 01				

This adaptor provides interchangeability with numerous components (especially watering accessories).

## 2299 Water Pistol

	Zamak, Nickel-plated brass, NBR				<b>H</b>	<b>L</b>	<b>kg</b>
					140	126	0.471
					2299 12 01		

This pistol allows independent control of:  
- the flow rate (trigger)  
- type of jet (adjustable to a fine mist) by the adjustable Probe

## 2299 Adjustable Nozzle

	Nickel-plated brass, NBR				<b>L</b>	<b>kg</b>
					77.4	0.137
					2299 12 20	

This nozzle allows adjustment of the spray.