

Kuppler mit Innengewinde

mit Ventil


Coupleur avec filetage femelle

avec soupape

Coupling with female thread

with valve

CO KA 202 (E)



Type	Mat.-Nr.	SW	L	e	kg/10
CO KA 202-G $\frac{1}{8}$ EV	335.2061.020	12	28.0	2.7	0.140
CO KA 202-M5 EV	335.2071.080	9	26.0	2.7	0.100

Kuppler mit Aussengewinde

mit Ventil


Coupleur avec filetage male

avec soupape

Coupling with male thread

with valve

CO KA 203 (EV)



Type	Mat.-Nr.	SW	L	e	kg/10
CO KA 203-G $\frac{1}{8}$ EV	335.2081.020	11	28.0	2.7	0.130
CO KA 203-M5 EV	335.2091.080	9	26.0	2.7	0.090

Stecker mit Schlauchtülle

ohne Ventil


Embout avec douille cannelée pour tuyeau

sans soupape

Nipple with hose nozzle

without valve

COT 201 (E)



Type	Mat.-Nr.	L	e	kg/10
COT 201 LW 3 E	335.2250.030	28.0	2.0	0.025
COT 201-LW 4 E	335.2250.040	28.0	2.7	0.035

Stecker mit Innengewinde


ohne Ventil

Embout avec filetage femelle

sans soupape

Nipple with female thread

without valve

COT 202 (E)


Type	Mat.-Nr.	SW	L	e	kg/10
COT 202-G $\frac{1}{8}$ E	335.2260.020	13	19.0	2.7	0.080
COT 202-M5 E	335.2270.080	7	17.0	2.7	0.030

Stecker mit Aussengewinde


ohne Ventil

Embout avec filetage male

sans soupape

Nipple with male thread

without valve

COT 203 (E)


Type	Mat.-Nr.	SW	L	e	kg/10
COT 203-G $\frac{1}{8}$ E	335.2280.020	11	20.0	2.7	0.055
COT 203-M5 E	335.2290.080	7	20.0	2.7	0.025