








Accessories







3130 Tamper-Proof Safety Clip

| Technical Polymer | ØD |  |  |  |  |  |  | H | K | kg |
|---|----|---|---|---|---|---|---|-------|------|-------|
|  | 4 | 3130 04 01 | 3130 04 02 | 3130 04 03 | 3130 04 04 | 3130 04 05 | 3130 04 10 | 6.60 | 3.00 | 0.001 |
| | 6 | 3130 06 01 | 3130 06 02 | 3130 06 03 | 3130 06 04 | 3130 06 05 | 3130 06 10 | 7.80 | 3.10 | 0.001 |
| | 8 | 3130 08 01 | 3130 08 02 | 3130 08 03 | 3130 08 04 | 3130 08 05 | 3130 08 10 | 9.50 | 4.30 | 0.001 |
| | 10 | 3130 10 01 | 3130 10 02 | 3130 10 03 | 3130 10 04 | 3130 10 05 | 3130 10 10 | 10.80 | 4.20 | 0.002 |
| | 12 | 3130 12 01 | 3130 12 02 | 3130 12 03 | 3130 12 04 | 3130 12 05 | 3130 12 10 | 12.50 | 5.10 | 0.003 |
| | 14 | 3130 14 01 | 3130 14 02 | 3130 14 03 | 3130 14 04 | 3130 14 05 | 3130 14 10 | 12.50 | 5.10 | 0.004 |







3130 Tamper-Proof Safety Clip

| Technical Polymer | ØD |  |  |  |  |  |  | H | K | kg |
|---|---|---|---|---|---|---|---|-------|------|-------|
|  | 1/4 | 3130 56 01 | 3130 56 02 | 3130 56 03 | 3130 56 04 | 3130 56 05 | 3130 56 10 | 7.80 | 3.10 | 0.001 |
| | 3/8 | 3130 60 01 | 3130 60 02 | 3130 60 03 | 3130 60 04 | 3130 60 05 | 3130 60 10 | 10.80 | 4.20 | 0.002 |
| | 1/2 | 3130 62 01 | 3130 62 02 | 3130 62 03 | 3130 62 04 | 3130 62 05 | 3130 62 10 | 12.50 | 5.10 | 0.003 |
| | 5/32" (4 mm) and 5/16" (8 mm) also available. | | | | | | | | | |



3110 Coloured Release Button Covers

| Technical Polymer | ØD |  |  |  |  |  | kg |
|--|----|---|---|---|---|---|-------|
|  | 4 | 3110 04 00 | 3110 04 02 | 3110 04 03 | 3110 04 04 | 3110 04 05 | 0.001 |
| | 6 | 3110 06 00 | 3110 06 02 | 3110 06 03 | 3110 06 04 | 3110 06 05 | 0.001 |
| | 8 | 3110 08 00 | 3110 08 02 | 3110 08 03 | 3110 08 04 | 3110 08 05 | 0.001 |
| | 10 | 3110 10 00 | 3110 10 02 | 3110 10 03 | 3110 10 04 | 3110 10 05 | 0.001 |
| | 12 | 3110 12 00 | 3110 12 02 | 3110 12 03 | 3110 12 04 | 3110 12 05 | 0.001 |
| | 14 | 3110 14 00 | 3110 14 02 | 3110 14 03 | 3110 14 04 | 3110 14 05 | 0.002 |

3110 Coloured Release Button Covers

| Technical Polymer | ØD |  |  |  |  |  | kg |
|---|--|---|---|---|---|---|-------|
|  | 1/4 | 3110 56 00 | 3110 56 02 | 3110 56 03 | 3110 56 04 | 3110 56 05 | 0.001 |
| | 3/8 | 3110 60 00 | 3110 60 02 | 3110 60 03 | 3110 60 04 | 3110 60 05 | 0.001 |
| | 1/2 | 3110 62 00 | 3110 62 02 | 3110 62 03 | 3110 62 04 | 3110 62 05 | 0.001 |
| | 5/32" (4 mm) and 5/16" (8 mm) also available | | | | | | |

0605 Fluoropolymer Tape

| FKM |  | kg |
|--|---|-------|
|  | 0605 12 12 | 0.012 |
| Can be used for temperatures from - 250°C to +260°C. Chemically inert and resistant to gases, acids, solvents, hydrocarbons, oils, alkalines, steam, etc. Non-toxic, waterproof, self-lubricating. In accordance with CFR21. Can be used on all materials. Used to facilitate the preparation of leak-free threaded joints. Supplied on a reel: length = 12 m; width = 12.7 mm; thickness = 0.08 mm. | | |