

## 787TC

**No-Skive GlobalCore Compact Spiral™**

### Tough Cover

Sizes -4 to -6 exceed ISO 18752-AC  
Sizes -8 to -32 exceed ISO 18752-DC

### Primary Applications

On- & offshore, construction, injection moulding, mining

### Type Approvals

Details please find on pages **Ab-16** to **Ab-19**

### Applicable Specifications

Exceeds SAE 100R13 – ISO 3862 Type R13 –  
EN 856 Type R13 – ISO 18752-AC/DC

### Construction

Inner tube: Proprietary synthetic rubber  
Reinforcement: Two-braid steel wire for sizes -4 to -6,  
Four- or six-compact spiral steel wires for  
sizes -8 to -32  
Cover: Highly abrasion resistance  
MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C  
(sizes -4 to -6 up to +100 °C)

Exception: Air ..... max. +70 °C  
Water ..... max. +85 °C



- 1/2 the bend radius of SAE 100R13
- Constant working pressure of 35.0 MPa
- Reduced O.D. and new construction lead to superior flexibility
- 1/3 less effort to bend
- Weight reduction – up to 26 %
- Highly abrasion resistant **TOUGH COVER**
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

### Recommended Fluids

Petroleum based hydraulic fluids and lubricating oils.  
Wide Compatibility exceeding Column III, with additional  
chemical resistance, especially for diesel and biodiesel.  
Consult the chemical compatibility section on  
pages **Ab-26** to **Ab-34** for more detailed information.

### Fitting Series

Series 43/48 for sizes -4 and -6

Series 77 for sizes -8 up to -32



Part Number	Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	DN	Inch	Size	mm		max. working pressure MPa	psi	min. burst pressure MPa	psi		
787TC-4	6	1/4	4	6.3	13.0	35.0	5000	140.0	20000	50	0.31
787TC-6	10	3/8	-6	10.0	17.2	35.0	5000	140.0	20000	63	0.42
787TC-8	12	1/2	-8	12.7	21.1	35.0	5000	140.0	20000	90	0.67
787TC-10	16	5/8	-10	15.9	23.9	35.0	5000	140.0	20000	100	0.80
787TC-12	19	3/4	-12	19.1	27.9	35.0	5000	140.0	20000	120	1.16
787TC-16	25	1	-16	25.4	35.7	35.0	5000	140.0	20000	150	1.74
787TC-20	31	1 1/4	-20	31.8	44.9	35.0	5000	140.0	20000	210	2.89
787TC-24	38	1 1/2	-24	38.1	52.8	35.0	5000	140.0	20000	255	3.96
787TC-32	51	2	-32	50.8	67.6	35.0	5000	140.0	20000	318	6.50

Replace the hose when any deformation or damage on the hose cover are visible.  
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

<b>Parker</b> GLOBALCORE	787TC-16 25 mm (1") ISO 18752-DC · SAE J1754-1 Class A · MSHA IC 40/26	35,0 MPa (5000 PSI)	MADE IN ITALY	PARKERHOSE.COM PARKER.COM/CRIMPSOURCE
--------------------------	---	---------------------	---------------	--