


## Adapters

**CD45 Male female thread 45° elbow**

Male NPTF\* thread (SAE J476) / Female NPTF\* thread (SAE J476)

SAE 140339

\*Stainless Steel = NPT to prevent galling



Thread NPT/NPTF PTM	Thread NPT/NPTF PTF	D mm	N3 mm	N4 mm	Y mm	Weight (steel) g/1 piece	Adapter Steel	Adapter Stainless Steel	PN (bar)	
									S	SS
1/8-27	1/8-27	4.8	12	18	14.0	24	<b>1/8 CD45-S</b>	<b>1/8 CD45-SS</b>	350	350
1/4-18	1/4-18	7.1	16	27	19.0	57	<b>1/4 CD45-S</b>	<b>1/4 CD45-SS</b>	350	350
3/8-18	3/8-18	10.3	18	27	22.0	79	<b>3/8 CD45-S</b>	<b>3/8 CD45-SS</b>	310	310
1/2-14	1/2-14	13.5	23	34	27.0	141	<b>1/2 CD45-S</b>	<b>1/2 CD45-SS</b>	210	210
3/4-14	3/4-14	18.3	25	35	33.3	196	<b>3/4 CD45-S</b>	<b>3/4 CD45-SS</b>	210	210
1-11.5	1-11.5	23.8	29	44	41.0	380	<b>1 CD45-S</b>	<b>1 CD45-SS</b>	125	120
1 1/4-11.5	1 1/4-11.5	31.8	41	46	47.6	719	<b>1 1/4 CD45-S</b>	<b>1 1/4 CD45-SS</b>	100	100

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.