

**Other designs in series 1400**

The following other designs can be found from page:

► Brass / Steel

P. 50

**Technical Description**

Safety coupling 1/4" with a self-venting system according to ISO 6150 B. Self-venting takes place during disconnection – no risk of pressurised hoses being tossed around. When the sleeve is pulled back, the plug is released yet remains locked in. The coupling valve closes and the air is vented from the air line at the same time. Only then, by operating the sleeve again, can uncoupling take place safely. The system fulfils the requirements of ISO 4414 – increased safety standards in the work place. DIN EN 983. Ultra High Flow valve for optimum flow and low pressure drop.

Series 1400 with additional end connections available on request.

**Working Pressure\*\***

0-12 bar

\*\* maximum static working pressure with design factor 4 to 1.

**Material**

**Coupling:** Brass / Steel nickel plated

**Plug:** Steel nickel plated

**Seals:** NBR

**Technical Description**

**Connecting Force 0 bar:** 35 N

**Connecting Force 6 bar:** 75 N


**Safety Note**

Reliable functioning can only be guaranteed in conjunction with original Parker Rectus plugs made of steel.

**Working Temperature\***

-20°C up to +100°C (NBR) depending on the medium.




\* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Flow diagrams**



## Couplings – with valve




## Series 1400KE

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 <p>Male Thread</p>	G 1/4	19	64,5	9	26	1400KEAW13SPN
	G 3/8	21	64,5	9	26	1400KEAW17SPN
 <p>Female Thread</p>	G 1/4	19	61,5	9	26	1400KEIW13SPN
	G 3/8	19	61,5	9	26	1400KEIW17SPN
 <p>Hose Barb</p>	6 mm	19	82,5	25	26	1400KETF06SPN
	8 mm	19	82,5	25	26	1400KETF08SPN
	10 mm	19	82,5	25	26	1400KETF10SPN



## Plugs – without valve

## Series 23SF

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
 <p>Male Thread</p>	R 1/8	13	39	9		23SFAK10SXN
	R 1/4	14	42	12		23SFAK13SXN
	R 3/8	17	42	12		23SFAK17SXN
	R 1/2	22	48	17		23SFAK21SXN
 <p>Female Thread</p>	G 1/8	14	36	9		23SFIW10SXN
	G 1/4	17	36	9		23SFIW13SXN
	G 3/8	19	36	9		23SFIW17SXN
	G 1/2	24	39	12		23SFIW21SXN
 <p>Hose Barb</p>	6 mm		51	14	25	23SFTF06SXN
	8 mm		51	14	25	23SFTF08SXN
	9 mm		51	14	25	23SFTF09SXN
	10 mm		51	14	25	23SFTF10SXN
	13 mm		51	15	25	23SFTF13SXN