





V series valve island: Electrical multi-connector head module

	Description	Protection	Cable length	Weight (g)	Order code
	Guillotine type	Multi-connection head module		38	P2M2HEV0A
	Guillotine connector with flying leads multi-cable	IP65	2 m	335	P8LMH20M2A
			5 m	802	P8LMH20M5A
			9 m	1425	P8LMH20M9A
	Standard Sub-D 25 type	Multi-connection head module		60	P2M2HEV0D
	Sub-D 25 connector with flying leads multi-cable	IP40	3 m	435	P8LMH25M3A
			9 m	1425	P8LMH25M9A
		IP65	9 m	1425	P8LMH25B9A


V series valve island: Electrical field bus head modules for AS-i protocol





Standard AS-i protocol (up to 31 nodes) electrical head modules

	Electrical module for 8 outputs max.	Input connections	Weight (g)	Order code
	<ul style="list-style-type: none"> V series islands may have up to 8 solenoid pilots 2 nodes per module, 4 I / 4 O per node 	No input	150	P2M2HBVA10800
		8 M8 inputs	200	P2M2HBVA10808A
		8 inputs on 4 M12	200	P2M2HBVA10808B
	Electrical module for 4 outputs max.	Input connections	Weight (g)	Order code
	<ul style="list-style-type: none"> V series islands may have up to 4 solenoid pilots 1 node per module, 4 I / 4 O 	No input	150	P2M2HBVA10400
		8 inputs on 4 M12	200	P2M2HBVA10404B

AS-i version 2-1 protocol (up to 62 nodes) electrical head modules

	Electrical module for 6 outputs max.	Input connections	Weight (g)	Order code
	<ul style="list-style-type: none"> V series islands may have up to 6 solenoid pilots 2 nodes per module, 4 I / 3 O per node 	None	150	P2M2HBVA20600
		8 M8 inputs	200	P2M2HBVA20608A
		8 inputs on 4 M12	200	P2M2HBVA20608B

AS-i head module accessories

	Description	Connector type	Weight (g)	Order code
	Cable quick connect connector	M8 Male	25	P8CS0803J
		M12 Male - A coding	25	P8CS1204J
	« Y » shape	M12 Male - 2 x M12 Female	25	P8CSY1212A
	Addressing cable 1 meter	M12 Male - Jack	100	P8LS12JACK