











PVL-B & -C valve module for electric low power solenoid or air actuator

Valve module without actuator



For use with air-pilot connector or 1,2 W / 1,6 VA solenoid valve

Symbol	Description	Valve size	Connection	Weight (g)	Order code
 	5/2 single acting / Spring return	PVL-B	Push-in Ø 6 mm	125	PVL-B121606
			G 1/8	125	PVL-B121618
		PVL-C	Push-in Ø 8 mm	240	PVL-C121608
	5/2 single acting / Air spring return	PVL-B	G 1/4	240	PVL-C121619
			G 3/8	240	PVL-C121613
		PVL-C	Push-in Ø 8 mm	240	PVL-C121608
	5/2 single acting / Air spring return	PVL-B	G 1/4	240	PVL-B123606
			G 3/8	125	PVL-B123618
		PVL-C	Push-in Ø 8 mm	240	PVL-C123608
 	5/2 double acting	PVL-B	G 1/4	240	PVL-C123619
			G 3/8	240	PVL-C123613
		PVL-C	Push-in Ø 8 mm	230	PVL-C122608
	5/3 APB (All Ports Blocked)	PVL-B	G 1/4	230	PVL-C122619
			G 3/8	230	PVL-C122613
		PVL-C	Push-in Ø 8 mm	250	PVL-C127608
	5/3 Vented centre	PVL-B	G 1/4	130	PVL-B127606
			G 3/8	130	PVL-B127618
		PVL-C	Push-in Ø 8 mm	250	PVL-C127608
 	5/3 Vented centre	PVL-C	G 1/4	250	PVL-C128608
			G 3/8	250	PVL-C128619
		PVL-B	Push-in Ø 8 mm	250	PVL-C128608
	Double 3/2 Normally Closed (NC)	PVL-B	G 1/4	250	PVL-C128619
			G 3/8	250	PVL-C128619
		PVL-C	Push-in Ø 8 mm	250	PVL-C128608
	Double 3/2 Normally Closed (NC)	PVL-B	G 1/4	130	PVL-B125606
			G 3/8	130	PVL-B125618
		PVL-C	Push-in Ø 8 mm	250	PVL-C128608

PVL-C valve module for electric high power solenoid or air actuator

Valve module without actuator

For use with air-pilot connector or 6 W / 8,5 VA solenoid valve

Symbol	Description	Valve size	Connection	Weight (g)	Order code
 	5/2 single acting / Spring return	PVL-C	Push-in Ø 8 mm	250	PVL-C121408
			G 1/4	250	PVL-C121419
	5/2 single acting / Air spring return	PVL-C	Push-in Ø 8 mm	250	PVL-C123408
			G 1/4	250	PVL-C123419
	5/2 double acting	PVL-C	Push-in Ø 8 mm	240	PVL-C122408
			G 1/4	240	PVL-C122419

Each valve module is supplied with two tie rods for use in the "stacking" system.

The above valve operator can be either :

- Pneumatic, by adding one or two air pilot connectors including a Ø4 mm push-in fitting or a threaded M5 port ;
- Electric, by adding one or two 1,2 W / 1,6 VA solenoids (PVL-B or C) or 6 W / 8,5 VA (PVL-C).