Metal spool valves

G1/8 and G1/4 Body ported spool valves with excellent reliability. Viton seals as standard provide long service life even in arduous conditions.

- 43 series G1/8 body ported
- 53 series G1/4 body ported
- Stainless steel spool
- 3/2, 5/2 and 5/3 versions
- Viton body seals as standard
- Integral mounting holes



Operating information

Working pressure
Working temperature

Vacuum-10 bar -10 °C to +80 °C

Port size

G1/8 G1/4 43 series

Flow (Qmax);

43 series

53 series 510 l/min

53 series

1740 l/min

For technical information see CD

Air pilot operated valves, B53 Series

	Symbol	Туре	Actuator	Return	Size	Order code
	- M	3/2	Air pilot	Differential pilot	G1/4	B53003J
		5/2	Air pilot	Differential pilot	G1/4	B53004J

Push button operated valves, B43 / B53 Series

	•					
	Symbol	Туре	Actuator	Return	Size	Order code
9	Œ ŢŢ W	3/2	Button, black	Spring	G1/8 G1/4	B43003BXS B53003HXS
	(,	3/2	Button black	Air Pilot	G1/4	B53003HXP
	ŒŢŢŢW	3/2	Button black	Spring	G1/8	B43603BX
	ŒŢ ĬŢ W	3/2	Button red	Spring	G1/4	B53003HY
	□, i],w	3/2	Button, black	Button	G1/8 G1/4	B43003HXS B53003HX
	4 2 www	5/2	Button, black	Spring	G1/8 G1/4	B43004BXS B53004HXS
	!]],	5/2	Button, black	Button	G1/8 G1/4	B43004HXS B53004HX
	Œ ŢŢ	5/2	Button black	Air Pilot	G1/8 G1/4	B43004HXP B53004HXP
	### ### ### ##########################	5/3	Button closed centre	Button self centring	G1/4	B53004HXX
				·		·



Indicates stocked product.



Mechanically operated valves, B43 / B53 Series

Symbol	Туре	Actuator	Return	Size	Order code
	3/2	Plunger Plunger Plunger	Spring Spring Spring	G1/8 G1/8 G1/4	B43003CS B43603C B53003CS
$= \underbrace{1}_{T} \underbrace{\int_{T}^{4} \underbrace{\frac{2}{1}}_{513}}_{513} \mathbf{ww}$	5/2	Plunger Plunger	Spring Spring	G1/8 G1/4	B43004CS B53004CS
	3/2	Roller lever Roller lever Roller	Spring Spring Spring	G1/8 G1/8 G1/4	B43003RS B43603R B53003RS
	3/2	One way roller trip	Spring	G1/8	B43003RTS
⊙=\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	5/2	Roller lever Roller	Spring Spring	G1/8 G1/4	B43004RS B53004RS
○	5/2	Roller	Air Pilot	G1/8	B43004RP

Manually operated valves, B43/53 series

	Symbol	Туре	Actuator	Return	Size	Mid-position	Order code			
Single-pedal operated										
	/	3/2	Foot pedal	Spring	G1/8 G1/4		B43003FS B53003FS			
			Foot pedal	Foot Pedal	G1/4		B53003G			
	<u></u>	5/2	Foot pedal	Spring	G1/8 G1/4		B43004FS B53004FS			
			Foot pedal	Foot Pedal	G1/4		B53004G			
		5/3	Foot pedal	Foot Pedal	G1/4	Closed centre	B53004GX			
			Foot pedal	Foot Pedal	G1/4	Vented centre	B53004GY			

Diaphragm operated valves

	Symbol	Туре	Actuator	Return	Size	Mid-position	Order code
		3/2	Diaphragm	Spring	G1/8		B43003DF
		5/2	Diaphragm	Spring	G1/8		B43004DF

Palm lever operated valves

Symbol	Туре	Actuator	Return	Size	Mid-position	Order code
	3/2	Palm lever	Spring	G1/8		B43003ES



