



## BALWASH 1W

Balflex® Balwash 155°C (+311°F) 1W 22.0MPa - 10.1W00

High pressure, single wire braid reinforced high temperature car wash hose



#	inch	SAE Dash	ID mm	OD mm	MPa PSI	MPa PSI	MIN BEND RAD mm	KG kg/m
10.1W00.04	1/4"	-4	6,3	13,0	22,0 3200	90.0 12800	100	0,23
10.1W00.05	5/16"	-5	8,0	14,7	22,0 3200	85.0 12800	114	0,28
10.1W00.06	3/8"	-6	9,5	17,2	22,0 3200	72.0 12800	127	0,33
10.1W00.08	1/2"	-8	12,7	20,5	22,0 3200	64.0 12800	178	0,42

**INNER TUBE:** seamless hot water resistant synthetic rubber

**REINFORCEMENT:** 1 high tensile steel wire braid

**OUTER TUBE:** black wrapped, oil, weather and abrasion resistant wrapped pin-pricked synthetic rubber

**SAFETY FACTOR:** 4:1 in 1/4"; 3.9:1 in 5/16"; 3.3:1 in 3/8"; 2.9:1 in 1/2"

**APPLICATION:** high temperature and high pressure cleaning professional equipments

**TEMPERATURE RANGE:** 0°C (+32°F) +155°C (+311°F)

**COUPLINGS:** Balflex® 2-piece fittings serie 23 with 20 serie ferrules. Balflex® Multicrimp fittings serie BW23/BF21/P23

**BALFLEX BALWASH UNO 1W - 155°C / 311°F - DN6 - 1/4" - WP 22 MPa 3190 PSI**

## BALWASH 2W

Balflex® Balwash 155°C (+311°F) 2W 40.0MPa - 10.2W00

High pressure, double wire braid reinforced high temperature car wash hose



#	inch	SAE Dash	ID mm	OD mm	MPa PSI	MPa PSI	MIN BEND RAD mm	KG kg/m
10.2W00.04	1/4"	-4	6,3	14,7	40.0 5800	160.0 23200	100	0,38
10.2W00.05	5/16"	-5	8,0	16,5	40.0 5800	140.0 23200	114	0,45
10.2W00.06	3/8"	-6	9,5	18,7	40.0 5800	132.0 23200	127	0,53
10.2W00.08	1/2"	-8	12,7	21,9	40.0 5800	110.0 23200	178	0,65

**INNER TUBE:** seamless hot water resistant synthetic rubber

**REINFORCEMENT:** 2 high tensile steel wire braids

**OUTER TUBE:** black wrapped, oil, weather and abrasion resistant wrapped pin-pricked synthetic rubber

**SAFETY FACTOR:** 4:1 in 1/4"; 3.9:1 in 5/16"; 3.3:1 in 3/8"; 2.9:1 in 1/2"

**APPLICATION:** high temperature and high pressure cleaning professional equipments

**TEMPERATURE RANGE:** 0°C (+32°F) +155°C (+311°F)

**COUPLINGS:** Balflex® 2-piece fittings serie 23 with 20 serie ferrules. Balflex® Multicrimp fittings serie BW23/BF21/P23

**BALFLEX BALWASH DUE 2W - 155°C / 311°F - DN6 - 1/4" - WP 40 MPa 5800 PSI**