


# Female ORFS Swivel with Back Hexagon

23.44H4.

ISO 12151-1 / ISO 8434-3 / SAE J516



|              | hose | hose Ø | thread        | C cut off | W  | HEX |
|--------------|------|--------|---------------|-----------|----|-----|
| REFERENCE    | dash | inch   | inch          | mm        | mm | mm  |
| 23.44H4.0404 | -4   | 1/4"   | 9/16" – 18    | 28.2      | 14 | 17  |
| 23.44H4.0406 | -4   | 1/4"   | 11/16" – 16   | 31.7      | 17 | 22  |
| 23.44H4.0606 | -6   | 3/8"   | 11/16" – 16   | 32.0      | 17 | 22  |
| 23.44H4.0608 | -6   | 3/8"   | 13/16" – 16   | 35.0      | 19 | 24  |
| 23.44H4.0808 | -8   | 1/2"   | 13/16" – 16   | 35.5      | 19 | 24  |
| 23.44H4.0810 | -8   | 1/2"   | 1" – 14       | 41.5      | 24 | 30  |
| 23.44H4.0812 | -8   | 1/2"   | 1.3/16" – 14  | 44.5      | 30 | 36  |
| 23.44H4.1010 | -10  | 5/8"   | 1" – 14       | 42.5      | 24 | 30  |
| 23.44H4.1012 | -10  | 5/8"   | 1.3/16" – 14  | 45.0      | 28 | 36  |
| 23.44H4.1212 | -12  | 3/4"   | 1.3/16" – 14  | 45.6      | 30 | 36  |
| 23.44H4.1216 | -12  | 3/4"   | 1.7/16" – 12  | 50.2      | 35 | 41  |
| 23.44H4.1616 | -16  | 1"     | 1.7/16" – 12  | 50.7      | 35 | 41  |
| 23.44H4.1620 | -16  | 1"     | 1.11/16" – 12 | 52.0      | 35 | 50  |
| 23.44H4.2020 | -20  | 1.1/4" | 1.11/16" – 12 | 54.5      | 41 | 50  |
| 23.44H4.2424 | -24  | 1.1/2" | 2" – 12       | 57.0      | 50 | 60  |

**MATERIAL:** Carbon Steel

**FINISH:** Chromium-(VI) Free plating /  
ROHS compliant

**VERSIONS:** Stainless Steel (add an 'S'  
at the end of the REFERENCE)