



Übergangsnippel Adaptateur femelle - mâle Male adaptor



SO 50040

Type -d -R	Mat.-Nr.	bar	M	SW	L	b	z	e	kg/100
R=Rohrgewinde (kegelig)	R=Filetage-gaz BSP (conique)		R=BSP thread (tapered)						
SO 50040-5-1/8	056.0401.082	250	8x1.0	10	17.0	11.0	7.0	3.5	0.710
SO 50040-6-1/8	056.0401.100	200	10x1.0	12	17.0	11.0	7.0	4.5	0.780
SO 50040-6-1/4	056.0401.110	200	10x1.0	14	21.0	15.0	9.0	4.5	1.800
SO 50040-6-3/8	056.0401.120	200	10x1.0	17	20.0	14.0	7.6	4.5	2.270
SO 50040-6-1/2	056.0401.125	200	10x1.0	22	23.0	17.0	8.8	4.5	4.450
SO 50040-8-1/8	056.0401.160	200	12x1.0	14	18.0	11.0	7.0	6.0	0.880
SO 50040-8-1/4	056.0401.170	200	12x1.0	14	22.0	15.0	9.0	6.5	1.460
SO 50040-8-3/8	056.0401.180	200	12x1.0	17	22.0	15.0	8.6	6.5	2.810
SO 50040-8-1/2	056.0401.185	200	12x1.0	22	26.0	19.0	10.8	6.5	4.970
SO 50040-10-1/8	056.0401.265	160	14x1.0	17	18.5	11.5	7.5	6.0	1.450
SO 50040-10-1/4	056.0401.270	160	14x1.0	17	22.0	15.0	9.0	8.5	1.590
SO 50040-10-3/8	056.0401.280	160	14x1.0	17	22.0	15.0	8.6	8.5	2.320
SO 50040-10-1/2	056.0401.285	160	14x1.0	22	23.0	16.0	7.8	8.5	4.650
SO 50040-12-1/4	056.0401.380	160	16x1.0	19	23.0	16.0	10.0	8.5	1.980
SO 50040-12-3/8	056.0401.390	160	16x1.0	19	22.0	15.0	8.6	10.5	2.200
SO 50040-12-1/2	056.0401.400	160	16x1.0	22	26.0	19.0	10.8	10.5	4.810
SO 50040-15-3/8	056.0401.532	100	20x1.5	24	24.0	16.0	9.6	10.5	3.490
SO 50040-15-1/2	056.0401.534	100	20x1.5	24	27.0	19.0	10.8	13.0	4.260
SO 50040-15-3/4	056.0401.536	100	20x1.5	27	27.5	19.5	10.0	13.0	7.960
SO 50040-18-1/2	056.0401.646	100	24x1.5	30	29.0	21.0	12.8	13.5	6.600
SO 50040-18-3/4	056.0401.648	100	24x1.5	30	29.5	21.5	12.0	15.0	8.540
SO 50040-22-3/4	056.0401.768	64	28x1.5	36	29.5	21.5	12.0	19.0	9.330

Übergangsnippel NPT Adaptateur femelle - mâle NPT Male adaptor NPT



SO 50040 NPT

Type -d -RNPT	Mat.-Nr.	bar	M	SW	L	b	z	e	kg/100
RNPT=NPT Gewinde	RNPT=Filetage NPT		RNPT=NPT thread						
SO 50040-5-1/8 NPT	056.0402.082	250	8x1.0	10	19.0	13.0	8.9	3.5	0.850
SO 50040-6-1/8 NPT	056.0402.100	200	10x1.0	12	19.0	13.0	8.9	5.0	0.850
SO 50040-6-1/4 NPT	056.0402.110	200	10x1.0	14	23.0	17.0	11.2	4.5	2.050
SO 50040-8-1/4 NPT	056.0402.170	200	12x1.0	14	24.0	17.0	11.2	6.5	1.640
SO 50040-10-1/4 NPT	056.0402.270	160	14x1.0	17	24.0	17.0	11.2	8.5	1.730
SO 50040-10-3/8 NPT	056.0402.280	160	14x1.0	17	24.0	17.0	11.0	8.5	2.610
SO 50040-12-1/4 NPT	056.0402.380	160	16x1.0	19	25.0	18.0	12.2	8.5	2.110
SO 50040-12-3/8 NPT	056.0402.390	160	16x1.0	19	25.0	18.0	12.0	10.5	2.480
SO 50040-12-1/2 NPT	056.0402.400	160	16x1.0	22	29.0	22.0	13.9	10.5	5.520
SO 50040-15-1/2 NPT	056.0402.534	100	20x1.5	24	30.0	22.0	13.9	13.0	4.850

Fortsetzung nächste Seite

Suite à la prochaine page

Continued on next page