





Nickel-Plated Brass Adaptors

0912 Equal Stud Elbow, Female BSPP and Metric Thread

Nickel-plated brass


C		E	G	J	L	kg
M5x0.8	0912 00 19	4	8	9	11	0.006
G1/8	0912 00 10	8	13	10	18.5	0.015
G1/4	0912 00 13	11	17	12	22.5	0.028
G3/8	0912 00 17	11.5	21	15	25.5	0.043
G1/2	0912 00 21	14	26	19	30	0.073
G3/4	0912 00 27	16.5	32	22	35.5	0.143
G1	0912 00 34	18	38.5	28	40.5	0.166

0921 Equal Stud Elbow, Male/Female and Metric Thread




	Nickel-plated brass		C1	C2		E	G	H	J	L	kg
			M5x0.8	M5x0.8	0921 00 19	4	8	11	9	11	0.006

0913 Equal Stud Elbow, Male BSPT/ Female BSPP Thread



Nickel-plated brass

C1	C2		E	G	H	J	L	kg
R1/8	G1/8	0913 00 10	8	13	17	10	18.5	0.012
R1/4	G1/4	0913 00 13	11	17	22.5	12	22.5	0.026
R3/8	G3/8	0913 00 17	11.5	21	25.5	15	25.5	0.038
R1/2	G1/2	0913 00 21	14	26	30	19	30	0.064
R3/4	G3/4	0913 00 27	16.5	32	34.5	22	35.5	0.098
R1	G1	0913 00 34	18	38.5	40.5	28	40.5	0.000


0922 Equal Stud Elbow, Male Metric Thread

	Nickel-plated brass	C		H	J	L	kg
		M5x0.8	0922 00 19	11	9	11	0.010
							

0914 Equal Stud Elbow, Male BSPT Thread







Nickel-plated brass




C		H	J	L	kg
R1/8	0914 00 10	17	10	17	0.012
R1/4	0914 00 13	22.5	12	22.5	0.027
R3/8	0914 00 17	25.5	15	25.5	0.035
R1/2	0914 00 21	30	19	30	0.056
R3/4	0914 00 27	34.5	22	34.5	0.104
R1	0914 00 34	40.5	28	40.5	0.156

Nickel-Plated Brass Adaptors




0910 Equal Y, Female BSPP Thread

	Nickel-plated brass 	C		E	F	H	kg
		G1/8	0910 00 10	8	13	12	0.018
		G1/4	0910 00 13	11	17	14	0.033
		G3/8	0910 00 17	11.5	20	16	0.045
		G1/2	0910 00 21	14	25	19	0.083




0911 Equal Y, Male BSPT/Female BSPP Thread

	Nickel-plated brass 	C1	C2		E	F	H	kg
		R1/8	G1/8	0911 00 10	8	13	12	0.022
		R1/4	G1/4	0911 00 13	11	17	14	0.038
		R3/8	G3/8	0911 00 17	11.5	20	16	0.050
		R1/2	G1/2	0911 00 21	14	25	19	0.103




0915 Equal Tee, Female BSPP and Metric Thread

	Nickel-plated brass 	C		E	G	H	J	L/2	kg
		M5x0.8	0915 00 19	4	8	11	9	11	0.010
		G1/8	0915 00 10	8	13	18.5	10	18.5	0.021
		G1/4	0915 00 13	11	17	22.5	12	22.5	0.042
		G3/8	0915 00 17	11.5	21	25.5	15	25.5	0.062
		G1/2	0915 00 21	14	26	30	19	30	0.099
		G3/4	0915 00 27	16.5	32	35.5	22	35.5	0.143
		G1	0915 00 34	18	38.5	40	28	40	0.244

0923 Equal Stud Branch Tee, Female/Male Metric Thread




	Nickel-plated brass 	C1	C2		E	G	H	J	L/2	kg
		M5x0.8	M5x0.8	0923 00 19	4	8	11	9	11	0.009

0916 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread









	Nickel-plated brass 	C1	C2		E	G	H	J	L/2	kg
		R1/8	G1/8	0916 00 10	8	13	17	10	18.5	0.019
		R1/4	G1/4	0916 00 13	11	17	23.5	13	22.5	0.038
		R3/8	G3/8	0916 00 17	11.5	21	25.5	15	25.5	0.076
		R1/2	G1/2	0916 00 21	14	26	30	19	30	0.091
		R3/4	G3/4	0916 00 27	16.5	32	34.5	22	35.5	0.140
		R1	G1	0916 00 34	18	38.5	40.5	28	40.5	0.237

Nickel-Plated Brass Adaptors









0924 Equal Stud Run Tee, Female/Male Metric Thread

	Nickel-plated brass	C1	C2		E	G	H	H1	J	L	kg
		M5x0.8	M5x0.8	 0924 00 19	4	8	11	11	9	11	0.009









0917 Equal Stud Run Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass	C1	C2		E	G	H	H1	J	L	kg
		R1/8	G1/8	 0917 00 10	8	13	17	18.5	10	18.5	0.025
		R1/4	G1/4	 0917 00 13	11	17	22.5	22.5	12	22.5	0.038
		R3/8	G3/8	 0917 00 17	11.5	21	25.5	25.5	15	25.5	0.058
		R1/2	G1/2	 0917 00 21	14	26	30	30	19	30	0.090
		R3/4	G3/4	 0917 00 27	16.5	32	34.5	35.5	22	35.5	0.177
		R1	G1	 0917 00 34	18	38.5	40.5	40.5	28	40.5	0.219









0927 Equal Tee, Male BSPT Thread

	Nickel-plated brass	C		H	J	L	kg
		R1/8	 0927 00 10	17	10	34	0.018
		R1/4	 0927 00 13	22.5	12	45	0.032
		R3/8	 0927 00 17	25.5	15	51	0.056
		R1/2	 0927 00 21	30	19	60	0.094
		R3/4	 0927 00 27	34.5	22	69	0.133
		R1	 0927 00 34	40.5	28	81	0.217

0928 Equal Stud Branch Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass	C1	C2		E	H	J	L	kg
		R1/8	G1/8	 0928 00 10	8	34	10	18.5	0.016
		R1/4	G1/4	 0928 00 13	11	45	12	22.5	0.044
		R3/8	G3/8	 0928 00 17	11.5	51	15	25.5	0.053
		R1/2	G1/2	 0928 00 21	14	60	19	30	0.111
		R3/4	G3/4	 0928 00 27	16.5	69	22	35.5	0.236
		R1	G1	 0928 00 34	18	81	28	40.5	0.225




0932 Equal Stud Run Tee, Male BSPT/Female BSPP Thread

	Nickel-plated brass	C1	C2		E	H	H1	J	L	kg
		R1/8	G1/8	 0932 00 10	8	17	18.5	10	17	0.016
		R1/4	G1/4	 0932 00 13	11	22.5	22.5	12	22.5	0.035
		R3/8	G3/8	 0932 00 17	11.5	25.5	25.5	15	25.5	0.055
		R1/2	G1/2	 0932 00 21	14	30	30	19	30	0.091
		R3/4	G3/4	 0932 00 27	16.5	34.5	35.5	22	34.5	0.080
		R1	G1	 0932 00 34	18	40.5	40.5	28	40.5	0.226

Nickel-Plated Brass Adaptors




0908

Equal Cross, Female BSPP Thread

	Nickel-plated brass		C		E	G	H	J	kg
			G1/8	0908 00 10	8	13	21	10	0.038
			G1/4	0908 00 13	11	17	25.5	13	0.073
			G3/8	0908 00 17	11.5	21	28	17	0.107
			G1/2	0908 00 21	14	26	33.5	21	0.189




0909

Equal Cross, Male BSPT/Female BSPP Thread

	<p>Nickel-plated brass</p> 	C1	C2		E	G	H	J	kg
		R1/8	G1/8	0909 00 10	8	13	18.5	10	0.034
		R1/4	G1/4	0909 00 13	11	17	23.5	13	0.068
		R3/8	G3/8	0909 00 17	11.5	21	26	17	0.099
		R1/2	G1/2	0909 00 21	14	26	31	21	0.168




0903

Reducer, Male/Female BSPP Thread

	Nickel-plated brass		C1	C2		E	F	kg
			G1/4	G1/8	0903 10 13	8	6	0.004
			G3/8	G1/4	0903 13 17	9	8	0.006
			G1/2	G3/8	0903 17 21	10	10	0.010
			G3/4	G1/2	0903 21 27	14	12	0.022
			G1	G3/4	0903 27 34	20	17	0.036


0904

Reducer, Male BSPT/Female BSPP Thread


	Nickel-plated brass		C1	C2		F	L	kg
			R1/4	G1/8	0904 10 13	14	16	0.010
			R3/8	G1/8	0904 10 17	17	16.5	0.020
				G1/4	0904 13 17	17	16.5	0.015
			R1/2	G1/4	0904 13 21	22	19.5	0.032
				G3/8	0904 17 21	22	19.5	0.025
			R3/4	G3/8	0904 17 27	27	23.5	0.057
				G1/2	0904 21 27	27	23.5	0.044


0905

Reducer, Male BSPP/Female BSPP and Metric Thread



Nickel-plated brass





C1	C2		E	F	L	kg
G1/8	M5x0.8	0905 19 10*	6	14	4.5	0.008
G1/4	G1/8	0905 10 13*	8	17	5	0.011
G3/8	G1/8	0905 10 17*	9	19	5	0.019
	G1/4	0905 13 17	9	19	5	0.013
G1/2	G1/4	0905 13 21	10	24	5.5	0.032
	G3/8	0905 17 21	10	24	5.5	0.022
G3/4	G3/8	0905 17 27	12	30	5.5	0.053
	G1/2	0905 21 27*	12	30	5.5	0.041

*Please contact us for detailed drawings of threads.



*Please contact us for detailed drawings of threads.

Nickel-Plated Brass Adaptors



0906 Increaser, Male BSPP and Metric/Female BSPP Thread

	Nickel-plated brass	C1	C2		E1	E2	F	L	kg
		M5x0.8	G1/8	0906 10 19	4	8	14	10	0.009
			G1/8	0906 00 10	6	8	14	10	0.011
		G1/8	G1/4	0906 10 13	6	11	17	14	0.016
			G3/8	0906 10 17	6	11.5	22	14.5	0.029
		G1/4	G1/4	0906 00 13	8	11	17	14	0.020
			G3/8	0906 13 17	8	11.5	22	14.5	0.032
			G1/2	0906 13 21	8	15	27	18	0.037
		G3/8	G3/8	0906 00 17	9	11.5	22	14.5	0.034
			G1/2	0906 17 21	9	14	27	18	0.038
		G1/2	G1/2	0906 00 21	10	14	27	18	0.054



0907 Equal Extended Adaptor, Male/Female BSPP Thread

	Nickel-plated brass	C		E	F	L	kg
		G1/8	0907 00 10	6	14	16	0.015
			0907 00 10 01	6	14	36	0.029
		G1/4	0907 00 13	8	17	26	0.032
			0907 00 13 01	8	17	43	0.046

0920 Bulkhead Connector, Female BSPP and Metric Thread

	Nickel-plated brass	C	C1		F	F1	K _{max}	L	L1	ØT	kg
		M5x0.8	M10x1	0920 00 19	14	14	7	10.5	3.5	10.5	0.012
		G1/8	M16x1.5	0920 00 10	19	22	9	14	4	16.5	0.029
		G1/4	M20x1.5	0920 00 13	24	27	15	21	4	20.5	0.056
		G3/8	M26x1.5	0920 00 17	30	32	14	21	5	26.5	0.095
		G1/2	M28x1.5	0920 00 21	32	36	20	27	6	28.5	0.115



0900 Equal and Unequal Adaptor, Male BSPT Thread

	Nickel-plated brass	C1	C2		F	L	kg
			R1/8	0900 00 10	12	19.5	0.008
		R1/8	R1/4	0900 10 13	14	23.5	0.015
			R3/8	0900 10 17	17	24	0.020
		R1/4	R1/4	0900 00 13	14	27	0.017
			R3/8	0900 13 17	17	27.5	0.026
			R1/2	0900 13 21	22	30.5	0.044
		R3/8	R3/8	0900 00 17	17	28	0.026
			R1/2	0900 17 21	22	31	0.046
		R1/2	R1/2	0900 00 21	22	33.5	0.044
			R3/4	0900 21 27	27	37.5	0.084
		R3/4	R3/4	0900 00 27	27	40	0.079
			R1	0900 27 34	34	43	0.144
		R1	R1	0900 00 34	34	45.5	0.153

Nickel-Plated Brass Adaptors

0901

Equal and Unequal Adaptor, Male BSPP and Metric Thread

	Nickel-plated brass	C1	C2		E	E1	F	L	kg
		M5x0.8	M5x0.8	0901 00 19	4	4	8	11.5	0.002
		G1/8	G1/8	0901 19 10	4	6	14	14.5	0.008
		G1/8	G1/8	0901 00 10	6	6	14	16.5	0.009
		G1/4	G1/4	0901 10 13	6	8	17	19	0.016
		G1/4	G1/4	0901 00 13	8	8	17	21	0.019
		G3/8	G3/8	0901 13 17	8	9	19	22	0.023
		G3/8	G3/8	0901 00 17	9	9	19	23	0.025
		G1/2	G1/2	0901 17 21	9	10	24	24.5	0.038
		G1/2	G1/2	0901 00 21	10	10	24	25.5	0.041



0192

Unequal Straight Adaptor, Male BSPT/BSPP Thread

	Nickel-plated brass	C1	C2		E	F	L	kg
		R1/8	G1/4	0192 10 13	9.5	17	23.5	0.019
		G1/4	G1/4	0192 13 13	9.5	17	27.5	0.024
		G1/2	G1/2	0192 13 21	11	27	31.5	0.068
		G1/4	G1/4	0192 17 13	9.5	17	28	0.025
		G1/2	G1/2	0192 17 21	11	27	31.5	0.061
		G1/2	G1/2	0192 21 21	11	27	34	0.061



0902

Equal and Unequal Adaptor, Female BSPP and Metric Thread

	Nickel-plated brass	C1	C2		F	L	kg
		M5x0.8	M5x0.8	0902 00 19	8	11	0.003
		G1/8	G1/8	0902 19 10	14	13	0.009
		G1/8	G1/8	0902 00 10	14	15	0.010
		G1/4	G1/4	0902 10 13	17	19.5	0.017
		G3/8	G3/8	0902 10 17	22	20	0.028
		G1/4	G1/4	0902 00 13	17	22	0.019
		G3/8	G3/8	0902 13 17	22	23	0.031
		G1/2	G1/2	0902 13 21	27	27	0.033
		G3/8	G3/8	0902 00 17	22	24	0.034
		G1/2	G1/2	0902 17 21	27	27.5	0.037
		G1/2	G1/2	0902 00 21	27	30	0.050
		G3/4	G3/4	0902 21 27	30	30	0.077
		G3/4	G3/4	0902 00 27	30	32	0.080

0191

Tailpiece Adaptor for Rubber Hose, Male BSPP Thread

	Nickel-plated brass	ØD	ØD1	C		E	F	K	L	kg
		4	6	G1/4	0191 04 13	9.5	17	5	22.5	0.019
		7	9	G1/4	0191 07 13	9.5	17	5	22.5	0.022
			9	G1/2	0191 07 21	11	27	7	29.5	0.065
		10	12.2	G1/4	0191 10 13	9.5	17	5	22.5	0.020
			12.2	G1/2	0191 10 21	11	27	7	29.5	0.061
		13	15.2	G1/4	0191 13 13	9.5	17	5	22.5	0.022
			15.2	G1/2	0191 13 21	11	27	7	29.5	0.058
		16	18.5	G1/2	0191 16 21	11	27	7	36.5	0.067


Nickel-Plated Brass Adaptors

0931

Tailpiece Adaptor for Rubber Hose, Male BSPP Thread



Nickel-plated brass



ØD	ØD1	C		E	F	K	L	kg
6	7	G1/8	0931 06 10	6	12	4	20	0.009
	7	G1/4	0931 06 13	8	14	5	20	0.013
7	8	G1/8	0931 07 10	6	12	4	20	0.009
	8	G1/4	0931 07 13	8	14	5	20	0.013
8	8	G3/8	0931 07 17	9	19	5	20	0.022
	9	G1/8	0931 08 10	6	12	4	20	0.009
9	9	G1/4	0931 08 13	8	14	5	20	0.014
	9	G3/8	0931 08 17	9	19	5	20	0.022
10	12	G1/4	0931 10 13	8	14	5	20	0.016
	12	G3/8	0931 10 17	9	19	5	20	0.024
15	12	G1/2	0931 10 21	10	22	6	22	0.031
	17	G3/8	0931 15 17	9	19	6	24	0.030
18	17	G1/2	0931 15 21	10	22	6	24	0.037
	20	G1/2	0931 18 21	10	22	6	24	0.039