


## 0206 Internal Hexagon Head Plug, Male BSPT Thread

Steel




C		E1	E2 max	E2 min	F	G	H	Kg
R1/8	<b>0206 10 00</b>	4	3.9	2.1	5	9.7	8	0.003
R1/4	<b>0206 13 00</b>	5	5.8	3.2	7	13.2	10	0.007
R3/8	<b>0206 17 00</b>	5	5.8	3.2	8	16.7	10	0.012
R1/2	<b>0206 21 00</b>	5	6.8	3.2	10	21	10	0.022
R3/4	<b>0206 27 00</b>	6	7.8	4.2	12	26.4	12	0.048
R1	<b>0206 34 00</b>	6	9.3	4.7	17	33.2	12	0.085
R1 1/4	<b>0206 42 00</b>	11.5	9.8	5.2	22	41.9	18	0.166
R1 1/2	<b>0206 49 00</b>	11.5	9.8	5.2	24	47.8	20	0.222

For BSPT plugs, from 1/2" - 1 1/2" inclusive :  
Conforms to DIN 906.  
Thread conforms to EN 10226-1

## 0206 Internal Hexagon Head Plug, Male NPT Thread

Steel




C		E1	E2 max	E2 min	F	G	H	Kg
NPT1/16	<b>0206 08 00</b>	6	6.4	3.8	4	7.8	7	0.002
NPT1/8	<b>0206 11 00</b>	6	5	3.2	5	10.2	8	0.003
NPT1/4	<b>0206 14 00</b>	8	7.2	4.4	6	13.6	10	0.007
NPT3/8	<b>0206 18 00</b>	8	7.5	4.7	8	17	11	0.012
NPT1/2	<b>0206 22 00</b>	8	9.9	6.3	10	21.2	13	0.023
NPT3/4	<b>0206 28 00</b>	11	10.4	6.8	14	26.6	17	0.048
NPT1	<b>0206 35 00</b>	13	12.4	8	17	33.2	19	0.082

Conforms to ANSI B1.20.1

## 0210 Hex Head Plug, Male BSPP and Metric Thread

Steel




C		E	F	G	H	Kg
M8x1.25	<b>0210 57 00</b>	8	14	12	15	0.011
G1/8	<b>0210 10 00</b>	8	14	14	15	0.013
G1/4	<b>0210 13 00</b>	12	19	18	21	0.031
G3/8	<b>0210 17 00</b>	12	22	22	21	0.046
G1/2	<b>0210 21 00</b>	14	27	26	24	0.078
G3/4	<b>0210 27 00</b>	16	32	32	27	0.133
G1	<b>0210 34 00</b>	18	41	39	33	0.270

Profile of head undercut conforms to DIN 3852-1, form D/E.  
BSPP threads, ISO 228-1.  
Parallel metric threads, NFE 03-054

## 0216 Hex Head Plug, Male BSPT Thread

Steel




C		F	H	Kg
R1/8	<b>0216 10 00</b>	13	16	0.012
R1/4	<b>0216 13 00</b>	17	19	0.023
R3/8	<b>0216 17 00</b>	19	21	0.038
R1/2	<b>0216 21 00</b>	22	23	0.060

BSPT thread conforms to EN 10226-1

## 0216 Hex Head Plug, Male NPT Thread

Steel



C		F	H	Kg
NPT1/8	<b>0216 11 00</b>	13	16	0.012
NPT1/4	<b>0216 14 00</b>	17	19	0.023
NPT1/2	<b>0216 22 00</b>	22	23	0.060