


# Mini Series


Single Shut-Off




Double Shut-Off











## 0171 Coupler, Male BSPT and Parallel Metric Thread



Technical polymer, nickel-plated brass, NBR







	C		Colour	F	L	kg	
	M7x1	0171 02 55 01		10	21	0.007	
	R1/8	0171 02 10 01		10	21	0.010	
	2	R1/8	0171 02 10 02		10	21	0.010
		R1/8	0171 02 10 03		10	21	0.010
		R1/8	0171 02 10 04		10	21	0.010
		R1/8	0171 02 10 05		10	21	0.010





Single shut-off

Mini Series (DN 2): single shut-off = 165 NL/min





## 0171 Coupler, Straight-Through, Male BSPT Thread

	<p>Technical polymer, nickel-plated brass, NBR</p> 		<b>C</b>		<b>Colour</b>	<b>F</b>	<b>G</b>	<b>L</b>	<b>kg</b>							
										R1/8	0171 03 10 01		13	17	24.5	0.020
										R1/8	0171 03 10 02		13	17	24.5	0.020
										R1/8	0171 03 10 03		13	17	24.5	0.020
										R1/8	0171 03 10 04		13	17	24.5	0.020
										R1/8	0171 03 10 05		13	17	24.5	0.020
Straight-through																





## 0183 Probe, Valved, Male BSPT Thread

	Nickel-plated brass, NBR	 <b>C</b> 	<b>F</b>	<b>L</b>	<b>kg</b>
		2 R1/8 <b>0183 02 10</b>	10	13	0.007
	Probe with shut-off				

## 0184 Probe, Straight-Through, Male BSPT Thread


			<b>C</b>		<b>F</b>	<b>L</b>	<b>kg</b>
		2	R1/8	0184 02 10	10	13	0.006
Probe without shut-off							

## 0181 Probe without Shut-off, Male BSPT Thread


	<p>Nickel-plated brass</p> 		ØD	ØD1		L	L1	kg
		2	3	3.3	0181 03 04	11.5	13.5	0.010
		Probe without shut-off						

# Mini Series

Single Shut-Off







Double Shut-Off



## 0181 Probe, Straight-Through with Barb Connection for Polyamide (PA) Tubing

	Nickel-plated brass		$\overline{\text{DN}}$	$\overline{\text{ØD}}$	$\overline{\text{ØD1}}$		$\overline{\text{L}}$	$\overline{\text{kg}}$
			3	4	4.7	0181 04 06	19	0.005
			Probe without shut-off					

## 0180 Probe, Straight-Through with Barb Connection for Flexible Tubing

	Nickel-plated brass			$\varnothing D$	$\varnothing D1$		<b>L</b>	<b>kg</b>
			3	4	6	0180 04 00	19	0.007
				5	6.5	0180 05 00	19	0.007
			Probe without shut-off					

## 3150 Probe, Straight-Through with LF 3000® Push-In Connection

	Nickel-plated brass, NBR		$\overline{\text{DN}}$	$\overline{\text{ØD}}$		$\overline{\text{G}}$	$\overline{\text{L}}$	$\overline{\text{L1}}$	$\overline{\text{kg}}$
			3	4	3150 00 61	8.5	39	18	0.008
			Probe without shut-off						