


2440D / 2440N – Ultra-high pressure hose









CONSTRUCTION

Core tube : DN 3-8: Polyoxymethylene; DN 10-25: Polyamide
 Pressure reinforcement : Four spiral layers of maximum tensile steel wire

Cover : Polyamide
 Standard colour : DN 3-8: blue; DN 10-25: black

TEMPERATURE RANGE -10°C up to +70°C

#											
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2440D-02V32	3	-02	3.0	1/8	7.9	207	30,000	518	75,000	100	0.12
2440D-025V32	4	-025	4.0	5/32	10.4	220	31,900	550	79,750	100	0.21
2440D-03V32	5	-03	4.8	3/16	11.5	180	26,100	450	65,250	130	0.28
2440D-04V32	6	-04	6.4	1/4	12.5	164	23,780	410	59,450	155	0.33
2440D-05V32	8	-05	8.1	5/16	15.1	150	21,750	375	54,375	175	0.44
2440N-06V30	10	-06	9.7	3/8	19.4	140	20,300	350	50,750	190	0.73
2440N-08V30	12	-08	12.8	1/2	22.5	130	18,850	325	47,125	200	0.94
2440N-12V30	20	-12	19.6	3/4	30.0	100	14,500	250	36,250	250	1.39
2440N-16V30	25	-16	25.0	1	37.0	90	13,050	225	32,625	300	2.00

NOTES