


## 3507 Swivel male 45° elbow

Male UN/UNF thread O-ring (ISO 11926) / NPSM Female swivel end (SAE J516)  
SAE 140357



Thread UN/UNF-2A A	Thread NPSM A1	C mm	C1 mm	C2 mm	D mm	D1 mm	M mm	W2 mm	N4 mm	Weight (steel) g/1 piece	Adapter Steel	PN (bar)
7/16-20	1/4-18	17.5	11.0	14.3	5.6	4.4	16	20	27	41	<b>3507-4-4</b>	350
9/16-18	3/8-18	22.2	14.0	17.5	8.7	7.5	21	26	29	62	<b>3507-6-6</b>	280
3/4-16	3/8-18	22.2	19.0	22.2	8.7	9.9	21	26	33	106	<b>3507-8-6</b>	280
3/4-16	1/2-14	25.4	19.0	22.2	11.9	9.9	21	30	33	141	<b>3507-8-8</b>	245
3/4-16	3/4-14	31.8	27.0	22.2	16.3	9.9	26	35	36	226	<b>3507-8-12</b>	140
7/8-14	1/2-14	25.4	22.0	25.4	11.9	12.3	22	30	39	154	<b>3507-10-8</b>	245
1 1/16-12	3/4-14	31.8	27.0	31.8	16.3	15.5	26	35	44	208	<b>3507-12-12</b>	140
1 5/16-12	1-11.5	38.0	33.3	38.0	21.4	21.4	29	39	47	408	<b>3507-16-16</b>	120

Parker Adapter are delivered with NBR elastomeric seals as standard. For more details on other seal materials see page O60.

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.