

Prestomatic Brass Push-In Fittings

F8UNPMB

Brass, NBR



ØD	C	
6x4	M10x1	F8UNPMB6M10
	M12x1.5	F8UNPMB6M12
	M16x1.5	F8UNPMB6M16
8x6	M22x1.5	F8UNPMB6M22
	M12x1.5	F8UNPMB8M12
	M14x1.5	F8UNPMB8M14
	M16x1.5	F8UNPMB8M16
10x7.5	M22x1.5	F8UNPMB8M22
	M12x1.5	F8UNPMB10M12
	M14x1.5	F8UNPMB10M14
	M16x1.5	F8UNPMB10M16
12x9	M22x1.5	F8UNPMB10M22
	M12x1.5	F8UNPMB12M12
	M16x1.5	F8UNPMB12M16
	M22x1.5	F8UNPMB12M22
16x12	M16x1.5	F8UNPMB16M16
	M22x1.5	F8UNPMB16M22

F2NPMB

Brass, NBR



ØD	C	
6x4	NPT1/8	F2NPMB6-1/8
	NPT1/4	F2NPMB6-1/4
	NPT3/8	F2NPMB6-3/8
8x6	NPT1/4	F2NPMB8-1/4
	NPT3/8	F2NPMB8-3/8
10x7.5	NPT1/4	F2NPMB10-1/4
	NPT1/2	F2NPMB10-1/2
12x9	NPT3/8	F2NPMB12-3/8
	NPT1/2	F2NPMB12-1/2

WEONPMB

Brass, NBR



ØD	DIN	C	
8x6	8L	M14x1.5	WEONPMB8-8L
	10L	M16x1.5	WEONPMB8-10L
	12L	M18x1.5	WEONPMB8-12L
12x9	12L	M18x1.5	WEONPMB12-12L

Port design to ISO8434-1 for steel tube and hoses.

WF8UNPMB

Brass, NBR



ØD	C	C1	
10x7.5	M16x1.5	M24x1.5	WF8UNPMB10M16
	M22x1.5	M24x1.5	WF8UNPMB10M22
12x9	M16x1.5	M24x1.5	WF8UNPMB12M16
	M22x1.5	M24x1.5	WF8UNPMB12M22

C8UNPMB

Brass, NBR



ØD	C	
6x4	M10x1	C8UNPMB6M10
	M12x1.5	C8UNPMB6M12
	M16x1.5	C8UNPMB6M16
	M22x1.5	C8UNPMB6M22
8x6	M12x1.5	C8UNPMB8M12
	M14x1.5	C8UNPMB8M14
	M16x1.5	C8UNPMB8M16
	M22x1.5	C8UNPMB8M22
10x7.5	M12x1.5	C8UNPMB10M12
	M16x1.5	C8UNPMB10M16
	M22x1.5	C8UNPMB10M22
	M12x1.5	C8UNPMB12M12
12x9	M16x1.5	C8UNPMB12M16
	M22x1.5	C8UNPMB12M22
16x12	M16x1.5	C8UNPMB16M16
	M22x1.5	C8UNPMB16M22

The body can be locked in the desired orientation with the locknut.

V8UNPMB

Brass, NBR



ØD	C	
10x7.5	M22x1.5	V8UNPMB10M22
12x9	M16x1.5	V8UNPMB12M16
	M22x1.5	V8UNPMB12M22
16x12	M22x1.5	V8UNPMB16M22

The body can be locked in the desired orientation with the locknut.

CWEONPMB

Brass, NBR



ØD	DIN	C	
8x6	15L	M22x1.5	CWEONPMB8-15L
	12L	M18x1.5	CWEONPMB12-12L
12x9	15L	M22x1.5	CWEONPMB12-15L

Port design to ISO8434-1 for steel tube or hoses.

CS8UNPMB

Brass, NBR



ØD	C	
10x7.5	M22x1.5	CS8UNPMB10M22
12x9	M16x1.5	CS8UNPMB12M16
	M22x1.5	CS8UNPMB12M22

The body can be locked in the desired orientation with the locknut.

Prestomatic Brass Push-In Fittings

S8UNPMB

Brass, NBR



ØD	C	
8x6	M16x1.5	S8UNPMB8M16
	M22x1.5	S8UNPMB8M22
10x7.5	M16x1.5	S8UNPMB10M16
	M22x1.5	S8UNPMB10M22
12x9	M16x1.5	S8UNPMB12M16
	M22x1.5	S8UNPMB12M22

The body can be locked in the desired orientation with the locknut.

R8UNPMB

Brass, NBR



ØD	C	
8x6	M16x1.5	R8UNPMB8M16
	M22x1.5	R8UNPMB8M22
10x7.5	M16x1.5	R8UNPMB10M16
	M22x1.5	R8UNPMB10M22
12x9	M16x1.5	R8UNPMB12M16
	M22x1.5	R8UNPMB12M22

The body can be locked in the desired orientation with the locknut.

S8UNPMBPPAM

Brass, NBR



ØD	C	
10x7.5	M16x1.5	S8UNPMB10PPAM16
	M22x1.5	S8UNPMB10PPAM22
12x9	M16x1.5	S8UNPMB12PPAM16
	M22x1.5	S8UNPMB12PPAM22

Test Point thread = M16x1.5

The body can be locked in the desired orientation with the locknut.

R8UNPMBPPA

Brass, NBR



ØD	C	
12x9	M16x1.5	R8UNPMB12M16PPA
	M22x1.5	R8UNPMB12M22PPA

Test Point thread = M16x1.5

The body can be locked in the desired orientation with the locknut.

R8UNPMBPPAM

Brass, NBR



ØD	C	
12x9	M16x1.5	R8BPPAM16-12
	M22x1.5	R8BPPAM22-12

Test Point thread = M16x1.5

The body can be locked in the desired orientation with the locknut.

HNPMB

Brass, NBR



ØD	
6x4	HNPMB6
8x6	HNPMB8
10x7.5	HNPMB10
12x9	HNPMB12
16x12	HNPMB16

WNPMB

Brass, NBR



ØD	C	
6x4	M18x1.5	WNPMB6
8x6	M20x1.5	WNPMB8
10x7.5	M22x1.5	WNPMB10
12x9	M24x1.5	WNPMB12

T2ENPMB

Brass, NBR



ØD	ØD1	
6x4	8	T2ENPMB6
8x6	8	T2ENPMB8
10x7.5	12	T2ENPMB10
12x9	12	T2ENPMB12

D1

JNPMB

Brass, NBR



ØD	
6x4	JNPMB6
8x6	JNPMB8
10x7.5	JNPMB10
12x9	JNPMB12
16x12	JNPMB16