










## PVL-B & -C valve module for electric low power solenoid or air actuator

Valve module without actuator





For use with air-pilot connector or 1,2 W / 1,6 VA solenoid valve

Symbol	Description	Valve size	Connection	Weight (g)	Order code
 	5/2 single acting / Spring return	PVL-B	Push-in Ø 6 mm	125	<b>PVL-B111606</b>
			G 1/8	125	<b>PVL-B111618</b>
		PVL-C	Push-in Ø 8 mm	240	<b>PVL-C111608</b>
			G 1/4	240	<b>PVL-C111619</b>
			G 3/8	240	<b>PVL-C111613</b>
	5/2 single acting / Air spring return	PVL-B	Push-in Ø 6 mm	125	<b>PVL-B113606</b>
			G 1/8	125	<b>PVL-B113618</b>
		PVL-C	Push-in Ø 8 mm	240	<b>PVL-C113608</b>
			G 1/4	240	<b>PVL-C113619</b>
			G 3/8	240	<b>PVL-C113613</b>
 	5/2 double acting	PVL-B	Push-in Ø 6 mm	120	<b>PVL-B112606</b>
			G 1/8	120	<b>PVL-B112618</b>
		PVL-C	Push-in Ø 8 mm	230	<b>PVL-C112608</b>
			G 1/4	230	<b>PVL-C112619</b>
			G 3/8	230	<b>PVL-C112613</b>
	5/3 APB (All Ports Blocked)	PVL-B	Push-in Ø 6 mm	130	<b>PVL-B117606</b>
			G 1/8	130	<b>PVL-B117618</b>
		PVL-C	Push-in Ø 8 mm	250	<b>PVL-C117608</b>
			G 1/4	250	<b>PVL-C117619</b>
 	5/3 Vented centre	PVL-C	Push-in Ø 8 mm	250	<b>PVL-C118608</b>
			G 1/4	250	<b>PVL-C118619</b>
		PVL-B	Push-in Ø 6 mm	130	<b>PVL-B115606</b>
			G 1/8	130	<b>PVL-B115618</b>
	Double 3/2 Normally Closed (NC)	PVL-B	Push-in Ø 6 mm	130	<b>PVL-B115606</b>
			G 1/8	130	<b>PVL-B115618</b>
		PVL-C	Push-in Ø 8 mm	250	<b>PVL-C118608</b>
			G 1/4	250	<b>PVL-C118619</b>

## PVL-C valve module for electric high power solenoids or air actuator

Valve module without actuator

For use with air-pilot connector or 6 W / 8,5 VA solenoid valve

Symbol	Description	Valve size	Connection	Weight (g)	Order code
 	5/2 single acting / Spring return	PVL-C	Push-in Ø 8 mm	250	<b>PVL-C111408</b>
			G 1/4	250	<b>PVL-C111419</b>
		PVL-C	Push-in Ø 8 mm	250	<b>PVL-C113408</b>
			G 1/4	250	<b>PVL-C113419</b>
	5/2 single acting / Air spring return	PVL-C	Push-in Ø 8 mm	250	<b>PVL-C113408</b>
			G 1/4	250	<b>PVL-C113419</b>
		PVL-C	Push-in Ø 8 mm	240	<b>PVL-C112408</b>
			G 1/4	240	<b>PVL-C112419</b>
	5/2 double acting	PVL-C	Push-in Ø 8 mm	240	<b>PVL-C112408</b>
			G 1/4	240	<b>PVL-C112419</b>
		PVL-C	Push-in Ø 8 mm	240	<b>PVL-C112408</b>
			G 1/4	240	<b>PVL-C112419</b>

Each valve module is supplied with two tie rods for use in the "stacking" system.

The above valve operator can be either :

- Pneumatic, by adding one or two air pilot connectors including a Ø4 mm push-in fitting or a threaded M5 port ;
- Electric, by adding one or two 1,2 W / 1,6 VA solenoids (PVL-B or C) or 6 W / 8,5 VA (PVL-C).