

Technical Data

max. Working Pressure 12 bar

Temperature Range -20°C up to +100°C (NBR)

Flow rate 1.225 l/min.
At input pressure 6 bar, pressure drop 0,6 barMaterial Coupling: Anodised Aluminium, Brass
nickel plated
Plug: Zinc plated steel
Seal: NBR

Coupler - Male Thread



C	Part Number
G 1/4	26KPAW13APX
G 3/8	26KPAW17APX
G 1/2	26KPAW21APX

Plug - Male Thread




C	Part Number
R 1/4	25SFAK13SXZ
R 3/8	25SFAK17SXZ
R 1/2	25SFAK21SXZ

Coupler - Female Thread



C	Part Number
G 1/4	26KPIW13APX
G 3/8	26KPIW17APX
G 1/2	26KPIW21APX

Plug - Female Thread



C	Part Number
G 1/4	25SFIW13SXZ
G 3/8	25SFIW17SXZ
G 1/2	25SFIW21SXZ

Coupler - Hose Barb



I.D. Hose	Part Number
6 mm	26KPTF06APX
8 mm	26KPTF08APX
10 mm	26KPTF10APX
13 mm	26KPTF13APX

Plug - Hose Barb



I.D. Hose	Part Number
6 mm	25SFTF06SXZ
8 mm	25SFTF08SXZ
10 mm	25SFTF10SXZ
13 mm	25SFTF13SXZ